



US 20150261259A1

(19) **United States**

(12) **Patent Application Publication**
Endo et al.

(10) **Pub. No.: US 2015/0261259 A1**

(43) **Pub. Date: Sep. 17, 2015**

(54) **ELECTRONIC DEVICE**

Publication Classification

(71) Applicant: **Semiconductor Energy Laboratory Co., Ltd.**, Kanagawa-ken (JP)

(51) **Int. Cl.**
G06F 1/16 (2006.01)

(72) Inventors: **Akio Endo**, Atsugi (JP); **Shigeru ONOYA**, Isehara (JP); **Masaaki HIROKI**, Isehara (JP)

(52) **U.S. Cl.**
CPC **G06F 1/1652** (2013.01); **G06F 1/1618** (2013.01); **G06F 1/1641** (2013.01)

(73) Assignee: **Semiconductor Energy Laboratory Co., Ltd.**, Kanagawa-ken (JP)

(57) **ABSTRACT**

Provided is an electronic device with high portability and/or high browsability. The electronic device includes first and second support bodies, a first hinge, and a flexible display panel. The first hinge has a first rotation axis and connects the first and second support bodies to each other, and the first and second support bodies are capable of relatively rotating on the first rotation axis. The display panel includes at least first and second portions supported by the first and second support bodies, respectively; the first rotation axis and a first plane including the display surface overlapping with the first portion or a second plane including the display surface overlapping with the second portion are parallel to each other; and each of a distance between the first rotation axis and the first plane or the second plane is greater than zero.

(21) Appl. No.: **14/629,990**

(22) Filed: **Feb. 24, 2015**

(30) **Foreign Application Priority Data**

Feb. 28, 2014 (JP) 2014-039372
Oct. 28, 2014 (JP) 2014-218932

